



AVX931

1CH Video Server



FEATURES

- Turn your traditional analog camera into a network camera
- Powerful Remote Surveillance on Multiple Mobile Platforms
 - For mobile device platforms, iPad®, iPod®, iPhone®, BlackBerry®, Nokia® Symbian, Windows® Mobile & Android™ (with their built-in web browsers or EagleEyes)
 - For web browsers, Internet Explorer®, Mozilla Firefox®, Safari®, Google Chrome™ and Opera
 - For operating systems, Windows & Mac
 - For multiple device control, our CMS software, Video Viewer, is provided for free
- Remote configuration and status checking
- Real-time H.264 / MPEG4 / MJPEG compression
- Motion detection and event notification with FTP / Email / SMS
- External I/O alarm device connection
- Free CMS software with E-Map for multiple devices control & surveillance
- ONVIF standard supported to simplify system integration

SPECIFICATIONS

	AVX931
Video Input	1 channel for analog & digital products, 1.0 Vp-p 75 composite, BNC
Audio	1 channel audio input / 1 channel audio output
Alarm I/O	1 input / 1 output
Watch dog	Yes
RS-485 Port	Yes
Network Interface	Ethernet (10/100 Base-T)
Image Compression	H.264 / MPEG4 / JPEG
Video Adjustment	Brightness, Contrast, Saturation and Hue
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP
Resolution	704x480, 352x240 (NTSC) / 704x576, 352x288 (PAL)
Frame Rate	NTSC: 30, PAL: 25
Motion Trigger Recording	Yes
Motion Detection	3 adjustable factors



	AVX931
Trigger & Action	Triggered by GPIO Input or Motion detection, Action: E-mail video/images or video/images upload to FTP site
ONVIF	Yes
Mobile Phone support	Yes
Mac PC support	Yes
Multiple Video streaming	Yes (H.264 / MPEG4 / MJPEG)
Number of Online Users	10
Security	Multiple user access levels with password, IP address filtering
Speed Dome Control	Yes (AVTECH / PELCO-D / PELCO-P)
De-blocking	Yes
De-interlace	Yes
Security	Password protection
Power Source	DC12 V/1A
Current consumption (± 10mm)	About 0.6A
Operating Temperature	0°C~40°C
Dimensions (mm)**	118.6 x 75 x 28.6

* The specifications are subject to change without notice.

** Dimensional tolerance: (± 5mm)

Dimensions

